

SPOTLIGHT

SPOTLIGHT LIDER D 840 21W 23° GREY | ON/OFF

Article number: N001-K0001-RF840-H5-G23-ZA02_550-S1-AA1



COB



		opotingint
Light colour	4000 [K]	Track mou possible. A on enquiry power is 3
CRI	80	
Led chip flux	3122 [lm]	
Luminous flux	2809 [lm]	
System power	21 [W]	
Luminaire Efficiency	134 [lm/W]	
Beam angle	23°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Weight 1,03 [k	<g]< th=""></g]<>
Protection rating IP , IK , class IP 20,	IK 1,
Luminaire colour GREY	
Cover Plastic	>
Operating voltage 220-24	40V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024