

SPOTLIGHT

## SPOTLIGHT LIDER D 940 10W 60° GREY | ON/OFF

Article number: N001-K0001-RF940-H5-G60-ZA01\_250-S1-AA1



COB

1,03 [kg]

GREY

Plastic

IP 20, IK 1,

220-240V 50-60Hz



	Light colour	4000 [K]	Tr pc or pc
	CRI	90	
	Led chip flux	1208 [lm]	
	Luminous flux	1087 [lm]	
	System power	10 [W]	
	Luminaire Efficiency	109 [lm/W]	
	Beam angle	60°	
	Controller	ON/OFF	
	MacAdam	3 SDCM	

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024