


SPOTLIGHT LIDER D 935 21W 23° WHITE HI EFFICIENT ON/OFF

Article number: N001-K0003-BB935-H5-G23-ZA02_550-S1-AA3



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	90
Led chip flux Luminous flux	3341 [lm]
System power	3006 [lm]
Luminaire Efficiency	21 [W]
Beam angle	143 [lm/W]
Controller	23°
MacAdam	ON/OFF 3 SDCM
	3 3DCIVI
UMINAIRE	

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 37W.

LU

Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska