

SPOTLIGHT

SPOTLIGHT LIDER D 940 14W 15° WHITE | ON/OFF

Article number: N001-K0003-RF940-H5-G15-ZA01_350-S1-AA3





LED	СОВ	Spotlight LED
Light colour	4000 [K]	Track mounted LED s possible. Available in v on enquiry. Reflector b power is 37W.
CRI	90	
Led chip flux	1691 [lm]	
Luminous flux	1521 [lm]	
System power	14 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		
Weight	1,03 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: All data are typ

WHITE

Plastic

220-240V 50-60Hz

spotlight. Aluminium housing. Ceiling base installation white, black and grey. Any RAL palette colour available beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska