

LIDER C FAMILY

Article number: N002-K0001-RF827-H5-G15-ZA01_250-S1-AA1



IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic



LED	COB	Spot
Light colour	2700 [K]	Track possi on er powe
CRI	80	
Led chip flux	895-5811 [lm]	
Luminous flux	805-5229 [lm]	
System power	10-37 [W]	
Luminaire Efficiency	72-151 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	1,65 [kg]	

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 19.05.2024

SPOTLIGHT