

SPOTLIGHT LIDER C 940 25W 38° WHITE HI EFFICIENT ON/OFF

Article number: N002-K0003-BB940-H5-G38-ZA02_650-S1-AA3





CRI Led chip flux	0.0
	90
Luminous flux	4090 [lm]
System power	3681 [lm]
Luminaire Efficiency	25 [W]
Beam angle	147 [lm/W]
Controller	38°
MacAdam	ON/OFF
	3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 37W.

LU

Weight	1,65 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska