SPOTLIGHT LIDER A 940 14W 60° GREY HI EFFICIENT ON/OFF

Article number: N004-K0001-BB940-H5-G60-ZE51_350-S1-###

110 mm

∅ 107 mm

LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	90
Led chip flux	2260 [lm]
Luminous flux	2034 [lm]
System power	14 [W]
Luminaire Efficiency	145 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

CE EAC UKCA

Generated: 22.06.2024

+48 32 388 80 00

www.cora.pl
cora@cora.pl

Street: Ignatza Hakuby 18
41-914 Bytom, Polska