

SPOTLIGHT

SPOTLIGHT LIDER A 942 31W 38° GREY MEAT WHITE ON/OFF

Article number: N004-K0001-CC942-H5-G38-ZE51_800-S1-###



| Light colour4200 [K] MEAT WHITECRI90Led chip flux3040 [Im]Luminous flux2736 [Im]System power31 [W]Luminaire Efficiency88 [Im/W]Beam angle38°ControllerON/OFF | LED | COB |
|---|--------------|-----------|
| Led chip flux90Luminous flux3040 [lm]System power2736 [lm]Luminaire Efficiency31 [W]Beam angle88 [lm/W]Controller38°MacAdamON/OFF | Light colour | |
| Luminous flux3040 [lm]System power2736 [lm]Luminaire Efficiency31 [W]Beam angle88 [lm/W]Controller38°MacAdamON/OFF | | 90 |
| 2736 [lm] System power Luminaire Efficiency Beam angle Controller MacAdam | | 3040 [lm] |
| Luminaire Efficiency31 [W]Beam angle88 [Im/W]Controller38°MacAdamON/OFF | | 2736 [lm] |
| Beam angle 38° Controller ON/OFF MacAdam | | 31 [W] |
| Controller ON/OFF MacAdam | Beam angle | L 4 |
| MacAdam | Controller | |
| 3 SDCM | MacAdam | 3 SDCM |

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

| Weight | 0.7 [kg] |
|-----------------------------------|----------------------|
| Protection rating IP , IK , class | IP 20, IK 01, |
| Luminaire colour | GREY |
| Cover | Plastic |
| Operating voltage | 220-240V 50- 60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



Street: Ignatza Hakuby 18 41-914 Bytom, Polska