

### SPOTLIGHT

### SPOTLIGHT LIDER A 942 10W 38° GREY MEAT WHITE ON/OFF

Article number: N004-K0001-CC942-H5-G38-ZE61\_250-S1-###



LEDCOBLight colour4200 [K] MEATCRI90Led chip flux1023 [Im]Luminous flux920 [Im]System power10 [W]Luminaire Efficiency92 [Im/W]Beam angle38°ControllerON/OFFMacAdam3 SDCM		
Light colour4200 [K] MEAT WHITECRI90Led chip flux1023 [Im]Luminous flux920 [Im]System power10 [W]Luminaire Efficiency92 [Im/W]Beam angle38°ControllerON/OFF	3 SDCM	
Light colour4200 [K] MEAT WHITECRI90Led chip flux1023 [Im]Luminous flux920 [Im]System power920 [Im]Luminaire Efficiency92 [Im/W]Beam angle38°	ON/OFF	
Light colour 4200 [K] MEAT WHITE 90 Led chip flux 1023 [Im] Luminous flux 920 [Im] System power 10 [W] Luminaire Efficiency 92 [Im/W]	38°	
Light colour 4200 [K] MEAT WHITE 90 Led chip flux 1023 [Im] Luminous flux 920 [Im] System power 10 [W]	92 [lm/W]	
Light colour 4200 [K] MEAT CRI 90 Led chip flux 1023 [lm] Luminous flux 920 [lm]	10 [W]	
Light colour 4200 [K] MEAT WHITE 00 Led chip flux 1023 [lm]	920 [lm]	
Light colour 4200 [K] MEAT WHITE 90	1023 [lm]	
Light colour 4200 [K] MEAT WHITE	90	
LED COB	4200 [K] MEAT	
	COB	

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

## LUMINAIR

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

 $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024