

SPOTLIGHT

SPOTLIGHT LIDER A 930 21W 38° GREY CRI97 ON/OFF

Article number: N004-K0001-HI930-H5-G38-ZE51_550-S1-###



LED	COB	Spotligh
Light colour	3000 [K] CRI97	Track m possible on enqui power is
CRI	90	
Led chip flux	2402 [lm]	
Luminous flux System power	2161 [lm] 21 [W]	
Luminaire Efficiency	103 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		-
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note: A

GREY

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024