

## SPOTLIGHT LIDER A 940 21W 15° GREY PREMIUM WHITE ON/OFF

Article number: N004-K0001-PW940-HA-G15-ZE51\_550-S1-###



Light colour4000 [K] PREMIUM WHITECRI90Led chip flux2912 [lm]Luminous flux2620 [lm]System power21 [W]Luminaire Efficiency125 [lm/W]Beam angle450	LED	СОВ
CRI90Led chip flux2912 [im]Luminous flux2620 [im]System power21 [W]Luminaire Efficiency125 [im/W]Beam angle125 [im/W]	Light colour	
Luminous flux2912 [Im]System power2620 [Im]Luminaire Efficiency21 [W]Beam angle125 [Im/W]		
System power 21 [W] Luminaire Efficiency 125 [Im/W] Beam angle		2912 [lm]
Luminaire Efficiency 125 [lm/W] Beam angle		n. 10
Beam angle	Luminaire Efficiency	L 1
	Ű.	15°
Controller ON/OFF		ON/OFF
3 SDCM	indo iddini	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

### LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl  $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

