

## SPOTLIGHT

## SPOTLIGHT LIDER A 827 27W 60° GREY | ON/OFF

Article number: N004-K0001-RF827-H5-G60-ZE51\_700-S1-###



LED	COB	Spotlig
Light colour	2700 [K]	Track r possibl on enq power i
CRI	80 3772 [lm] 3394 [lm] 27 [W] 126 [lm/W] 60° ON/OFF 3 SDCM	
Led chip flux		
Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam		
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note:

GREY

Plastic

220-240V 50-60Hz

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024