

SPOTLIGHT

SPOTLIGHT LIDER A 830 21W 45° GREY | ON/OFF

Article number: N004-K0001-RF830-H5-G45-ZE51_550-S1-###



LED	СОВ	Spotl
Light colour	3000 [K]	Track
CRI	80 2994 [lm] 2694 [lm] 21 [W] 128 [lm/W] 45°	possik on en power
Led chip flux Luminous flux System power Luminaire Efficiency Beam angle		
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note

GREY

Plastic

220-240V 50-60Hz

tlight LED

k mounted LED spotlight. Aluminium housing. Ceiling base installation ible. Available in white, black and grey. Any RAL palette colour available nquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum er is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska