

SPOTLIGHT

SPOTLIGHT LIDER A 830 19W 60° GREY | ON/OFF

Article number: N004-K0001-RF830-H5-G60-ZE51_500-S1-###



LED	COB	Spo
Light colour	3000 [K]	Trac
CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle	80 2722 [lm] 2449 [lm] 19 [W] 129 [lm/W] 60°	poss on e pow
		Controller
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	No

GREY

Plastic

220-240V 50-60Hz

otlight LED

ack mounted LED spotlight. Aluminium housing. Ceiling base installation ssible. Available in white, black and grey. Any RAL palette colour available enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum wer is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska