

SPOTLIGHT

SPOTLIGHT LIDER A 835 25W 15° GREY | ON/OFF

Article number: N004-K0001-RF835-H5-G15-ZE51_650-S1-###



| LED | COB | Sp |
|-----------------------------------|---------------------|----------|
| Light colour | 3500 [K] | Tr |
| CRI | 80 | po on |
| Led chip flux | 3618 [lm] | po |
| Luminous flux System power | 3256 [lm] 25 [W] | |
| | | |
| Luminaire Efficiency | 130 [lm/W] | |
| Beam angle | 15° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | 1 |

GREY

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ower is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska