

SPOTLIGHT

SPOTLIGHT LIDER A 835 31W 38° GREY | ON/OFF

Article number: N004-K0001-RF835-H5-G38-ZE51_800-S1-###



| LED | COB | Spot |
|----------------------|------------|---------------|
| Light colour | 3500 [K] | Trac |
| CRI | 80 | poss on ei |
| Led chip flux | 4453 [lm] | pow |
| Luminous flux | 4007 [lm] | |
| System power | 31 [W] | |
| Luminaire Efficiency | 129 [lm/W] | |
| Beam angle | 38° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,7 [kg] | |

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

otlight LED

ck mounted LED spotlight. Aluminium housing. Ceiling base installation ssible. Available in white, black and grey. Any RAL palette colour available enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ver is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska