

# SPOTLIGHT LIDER A 840 21W 60° GREY | ON/OFF

Article number: N004-K0001-RF840-H5-G60-ZE51\_550-S1-###



LED	COB
Light colour	4000 [K]
CRI	80
Led chip flux	3122 [lm]
Luminous flux	2809 [lm]
System power	21 [W]
Luminaire Efficiency	134 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

### LUMINAIRE

Weight	0.7 [kg]
Protection rating IP , IK , class	IP 20, IK 01,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%  
System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 24.09.2024



+48 32 388 80 00



[www.cora.pl](http://www.cora.pl)

[cora@cora.pl](mailto:cora@cora.pl)



Street: Ignatza Hakuby 18

41-914 Bytom, Polska