

SPOTLIGHT

SPOTLIGHT LIDER A 850 27W 15° GREY | ON/OFF

Article number: N004-K0001-RF850-H5-G15-ZE51_700-S1-###



LED	COB	Spot
Light colour CRI	5000 [K] 80 4053 [lm] 3647 [lm] 27 [W] 135 [lm/W] 15°	Tracl poss on er powe
Luminous flux System power Luminaire Efficiency Beam angle		
Controller		ON/OFF
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	No

GREY

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024