

## SPOTLIGHT

## SPOTLIGHT LIDER A 850 10W 23° GREY | ON/OFF

Article number: N004-K0001-RF850-H5-G23-ZE61\_250-S1-###



LED	СОВ	Spo
Light colour	5000 [K]	Trac
CRI	80	poss on e
Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	1447 [lm] 1302 [lm] 10 [W] 130 [lm/W] 23° ON/OFF 3 SDCM	pow
LUMINAIRE		_
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

## otlight LED

ack mounted LED spotlight. Aluminium housing. Ceiling base installation ssible. Available in white, black and grey. Any RAL palette colour available enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum wer is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska