

SPOTLIGHT

SPOTLIGHT LIDER A 927 27W 45° GREY | ON/OFF

Article number: N004-K0001-RF927-H5-G45-ZE51_700-S1-###



LED	COB	Spotlig
Light colour	2700 [K]	Track m possible on enqu power is
CRI	80	
Led chip flux	3111 [lm]	
Luminous flux	2799 [lm] 27 [W] 104 [lm/W]	
System power		
Luminaire Efficiency		
Beam angle	45°	
Controller	ON/OFF 3 SDCM	
MacAdam		
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

ght LED

mounted LED spotlight. Aluminium housing. Ceiling base installation le. Available in white, black and grey. Any RAL palette colour available uiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska