

SPOTLIGHT

SPOTLIGHT LIDER A 930 23W 15° GREY | ON/OFF

Article number: N004-K0001-RF930-H5-G15-ZE51_600-S1-###



LED	COB	Sp			
Light colour CRI Led chip flux Luminous flux System power Luminaire Efficiency	3000 [K] 90 2767 [lm] 2490 [lm] 23 [W] 108 [lm/W]	Tra pos on pov			
			Beam angle	15°	
			Controller	ON/OFF	
			MacAdam	3 SDCM	
		LUMINAIRE		_	
Weight	0,7 [kg]				
Protection rating IP , IK , class	IP 20, IK 1,	N			

GREY

Plastic

220-240V 50-60Hz

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024