

SPOTLIGHT

SPOTLIGHT LIDER A 930 27W 45° GREY | ON/OFF

Article number: N004-K0001-RF930-H5-G45-ZE51_700-S1-###



LED	COB	Sp
Light colour	3000 [K]	Tra
CRI	90	pos on
Led chip flux	3227 [lm] 2904 [lm] 27 [W]	po
Luminous flux		
System power		
Luminaire Efficiency	108 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024