

SPOTLIGHT

SPOTLIGHT LIDER A 940 25W 15° GREY | ON/OFF

Article number: N004-K0001-RF940-H5-G15-ZE51_650-S1-###



LED	COB	Spotlig
Light colour	4000 [K]	Track m possible on enqu power is
CRI	90	
Led chip flux	3141 [lm]	
Luminous flux	2826 [lm]	
System power	25 [W]	
Luminaire Efficiency	113 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	Note:

GREY

Plastic

220-240V 50-60Hz

ght LED

mounted LED spotlight. Aluminium housing. Ceiling base installation le. Available in white, black and grey. Any RAL palette colour available uiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska