

SPOTLIGHT

SPOTLIGHT LIDER A 940 14W 60° GREY | ON/OFF

Article number: N004-K0001-RF940-H5-G60-ZE51_350-S1-###



| LED | COB | s |
|----------------------|------------|---|
| Light colour | 4000 [K] | Т |
| CRI | 90 | p |
| Led chip flux | 1691 [lm] | p |
| Luminous flux | 1521 [lm] | |
| System power | 14 [W] | |
| Luminaire Efficiency | 109 [lm/W] | |
| Beam angle | 60° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | _ |
| Weight | 0,7 [kg] | |

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024