

SPOTLIGHT LIDER A 825 27W 15° GREY BREAD ON/OFF

Article number: N004-K0001-VF825-H5-G15-ZE51_700-S1-###





COB

2500 [K] BREAD Light colour

CRI

3169 [lm] Led chip flux Luminous flux 2852 [lm] System power 27 [W] Luminaire Efficiency 106 [lm/W] Beam angle 15°

Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

0,7 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska