

## SPOTLIGHT

## SPOTLIGHT LIDER A 825 25W 23° GREY BREAD ON/OFF

Article number: N004-K0001-VF825-H5-G23-ZE51\_650-S1-###



Weight	0,7 [kg]
UMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	23°
Luminaire Efficiency	109 [lm/W]
System power	25 [W]
Luminous flux	2737 [lm]
Led chip flux	3042 [lm]
CRI	80
Light colour	2500 [K] BREAD
LED	COB

IP 20, IK 1,

220-240V 50-60Hz

GREY

Plastic

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

**OPTIONS** 

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024