

SPOTLIGHT LIDER A 825 21W 38° GREY BREAD ON/OFF

Article number: N004-K0001-VF825-H5-G38-ZE51_550-S1-###



COB

ON/OFF

3 SDCM



 Light colour
 2500 [K] BREAD

 CRI
 80

 Led chip flux
 2574 [Im]

 Luminous flux
 2316 [Im]

 System power
 21 [W]

 Luminaire Efficiency
 [Im/W]

 Beam angle
 38°

Beam angle
Controller
MacAdam

LUMINAIRE

Weight 0,7 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska