

SPOTLIGHT LIDER A 930 31W 15° BLACK HI EFFICIENT ON/OFF

Article number: N004-K0002-BB930-H5-G15-ZE52_800-S1-###





LED COB

Light colour 3000 [K] HI EFFICIENT

CRI

Led chip flux

Luminous flux 4956 [lm]

4460 [lm] System power

Luminaire Efficiency 144 [Im/W]

Beam angle

Controller 15°

ON/OFF MacAdam

3 SDCM

LUMINAIRE

Weight 0.7 [kg]

Protection rating IP , IK , class IP 20, IK 01,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-

60Hz

31 [W]

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

(€ EM 2K

Generated: 24 09 2024





