

SPOTLIGHT LIDER A 930 31W 23° BLACK HI EFFICIENT ON/OFF

Article number: N004-K0002-BB930-H5-G23-ZE52_800-S1-###





LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	30
Luminous flux	4956 [lm]
Lutilitous flux	4460 [lm]
System power	
Luminaire Efficiency	31 [W]
Luminal e Eniciency	144 [lm/W]
Beam angle	
Controller	23°
	ON/OFF
MacAdam	0.00014
	3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight 0,7 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 22.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska