

## SPOTLIGHT

# SPOTLIGHT LIDER A 930 23W 45° BLACK HI EFFICIENT ON/OFF

Article number: N004-K0002-BB930-H5-G45-ZE52\_600-S1-###



LED	СОВ
Light colour	3000 [K] HI EFFICIENT
CRI	EFFICIENT
Led chip flux	90
	3787 [lm]
Luminous flux	3408 [lm]
System power	n <i>a</i>
Luminaire Efficiency	23 [W]
	148 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	UN/OFF
	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

# LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024