

## SPOTLIGHT

# SPOTLIGHT LIDER A 935 25W 45° BLACK HI EFFICIENT ON/OFF

Article number: N004-K0002-BB935-H5-G45-ZE52\_650-S1-###



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	90
Led chip flux	90
	3904 [lm]
Luminous flux	3513 [lm]
System power	0010 [[[1]]
Luminaire Efficiency	25 [W]
Luminare Enciency	141 [lm/W]
Beam angle	
Controller	45°
	ON/OFF
MacAdam	0.0001
	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

# LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

