

SPOTLIGHT

SPOTLIGHT LIDER A 940 19W 60° BLACK HI EFFICIENT ON/OFF

Article number: N004-K0002-BB940-H5-G60-ZE52_500-S1-###



LED	СОВ
Light colour	4000 [K] HI EFFICIENT
CRI	LITIGILINI
Led chip flux	90
	3189 [lm]
Luminous flux	2870 [lm]
System power	19 [W]
Luminaire Efficiency	
Beam angle	151 [lm/W]
	60°
Controller	ON/OFF
MacAdam	3 SDCM
	5 500W

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024