

SPOTLIGHT

SPOTLIGHT LIDER A 827 10W 60° BLACK | ON/OFF

Article number: N004-K0002-RF827-H5-G60-ZE62_250-S1-###



LED	СОВ	5
Light colour	2700 [K]	Т
CRI	80	p
Led chip flux	1347 [lm]	p
Luminous flux	1212 [lm]	
System power	10 [W]	
Luminaire Efficiency	121 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		
Weight	0,7 [kg]	
	Light colour CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	Light colour2700 [K] CRI80Led chip flux1347 [m]Luminous flux1212 [m]System power10 [W]Luminaire Efficiency121 [lm/W]Beam angle60°ControllerON/OFFMacAdam3 SDCM

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024