

## SPOTLIGHT LIDER A 830 23W 15° BLACK | ON/OFF

Article number: N004-K0002-RF830-H5-G15-ZE52\_600-S1-###



|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 3000 [K]  |
| CRI                  | 80        |
| Led chip flux        | 3266 [lm] |
| Luminous flux        | 2939 [lm] |
| System power         | 23 [W]    |
| Luminaire Efficiency | [lm/W]    |
| Beam angle           | 15°       |
| Controller           | ON/OFF    |
| MacAdam              | 3 SDCM    |

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 0,7 [kg]         |
| Protection rating IP , IK , class | IP 20, IK 1,     |
| Luminaire colour                  | WHITE            |
| Cover                             | Plastic          |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska