

SPOTLIGHT

SPOTLIGHT LIDER A 830 31W 15° BLACK | ON/OFF

Article number: N004-K0002-RF830-H5-G15-ZE52_800-S1-###



| Light colour3000 [K] CRI80Led chip flux4355 [Im]Luminous flux3919 [Im]System power31 [W]Luminaire Efficiency126 [Im/W] | Spotli |
|---|--------------------------------------|
| Led chip flux4355 [lm]Luminous flux3919 [lm]System power31 [W] | Track i possib on eno power |
| Luminous flux3919 [lm]System power31 [W] | |
| System power 31 [W] | |
| | |
| Luminaire Efficiency 126 [Im/W] | |
| | |
| Beam angle 15° | |
| Controller ON/OFF | |
| MacAdam 3 SDCM | |
| LUMINAIRE | |
| Weight 0,7 [kg] | |

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024