

SPOTLIGHT

SPOTLIGHT LIDER A 835 25W 15° BLACK | ON/OFF

Article number: N004-K0002-RF835-H5-G15-ZE52_650-S1-###



LED	COB	Spot
Light colour	3500 [K]	Track
CRI	80	possi on en powe
Led chip flux Luminous flux System power	3618 [lm] 3256 [lm] 25 [W]	
Luminaire Efficiency	130 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

otlight LED

ck mounted LED spotlight. Aluminium housing. Ceiling base installation sible. Available in white, black and grey. Any RAL palette colour available enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum er is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska