

SPOTLIGHT

SPOTLIGHT LIDER A 835 23W 38° BLACK | ON/OFF

Article number: N004-K0002-RF835-H5-G38-ZE52_600-S1-###



LED	COB	Spotligh
Light colour	3500 [K]	Track mo possible on enqui power is
CRI	80	
Led chip flux	3340 [lm]	
Luminous flux	3006 [lm]	
System power	23 [W]	
Luminaire Efficiency	131 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024