

SPOTLIGHT

SPOTLIGHT LIDER A 850 21W 15° BLACK | ON/OFF

Article number: N004-K0002-RF850-H5-G15-ZE52_550-S1-###



LED	COB	Spotlig
Light colour	5000 [K] 80	Track n possibl on enq
CRI		
Led chip flux	3185 [lm]	power i
Luminous flux System power	2866 [Im] 21 [W] 136 [Im/W] 15° ON/OFF 3 SDCM	
Beam angle Controller		
MacAdam		
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

ight LED

mounted LED spotlight. Aluminium housing. Ceiling base installation ole. Available in white, black and grey. Any RAL palette colour available quiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska