

## SPOTLIGHT

## SPOTLIGHT LIDER A 850 27W 23° BLACK | ON/OFF

Article number: N004-K0002-RF850-H5-G23-ZE52\_700-S1-###



CRI80poss on en powerLuminous flux4053 [Im]System power3647 [Im]Luminaire Efficiency135 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	LED	COB	Spotligh
CH80Led chip flux4053 [Im]Luminous flux3647 [Im]System power27 [W]Luminaire Efficiency135 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	Light colour	5000 [K]	Track m
Led chip flux4053 [im]Luminous flux3647 [im]System power27 [W]Luminaire Efficiency135 [im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	CRI	80	possible. on enqui
System power27 [W]Luminaire Efficiency135 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	Led chip flux	4053 [lm]	power is
Luminaire Efficiency     135 [Im/W]       Beam angle     23°       Controller     ON/OFF       MacAdam     3 SDCM	Luminous flux	3647 [lm]	
Beam angle 23° Controller ON/OFF MacAdam 3 SDCM	System power	27 [W]	
Controller ON/OFF MacAdam 3 SDCM LUMINAIRE	Luminaire Efficiency	135 [lm/W]	
MacAdam 3 SDCM	Beam angle	23°	
LUMINAIRE	Controller	ON/OFF	
	MacAdam	3 SDCM	
			_
Weight 0,7 [kg]	Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

## ht LED

nounted LED spotlight. Aluminium housing. Ceiling base installation e. Available in white, black and grey. Any RAL palette colour available uiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum s 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska