

SPOTLIGHT

SPOTLIGHT LIDER A 850 14W 45° BLACK | ON/OFF

Article number: N004-K0002-RF850-H5-G45-ZE52_350-S1-###



LED	COB	Spo
Light colour	5000 [K]	Tra
CRI	80	pos on e
Led chip flux Luminous flux	2027 [lm] 1824 [lm] 14 [W] 130 [lm/W] 45° ON/OFF 3 SDCM	pow
System power		
Luminaire Efficiency		
Beam angle Controller		
MacAdam		
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024