

## SPOTLIGHT

## SPOTLIGHT LIDER A 930 21W 60° BLACK | ON/OFF

Article number: N004-K0002-RF930-H5-G60-ZE52\_550-S1-###



| LED                  | COB        | Spotlig                      |
|----------------------|------------|------------------------------|
| Light colour         | 3000 [K]   | Track r                      |
| CRI                  | 90         | possibl<br>on enq<br>power i |
| Led chip flux        | 2536 [lm]  |                              |
| Luminous flux        | 2282 [lm]  |                              |
| System power         | 21 [W]     |                              |
| Luminaire Efficiency | 109 [lm/W] |                              |
| Beam angle           | 60°        |                              |
| Controller           | ON/OFF     |                              |
| MacAdam              | 3 SDCM     |                              |
| LUMINAIRE            |            |                              |
| Weight               | 0,7 [kg]   |                              |

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

## Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024