

SPOTLIGHT

SPOTLIGHT LIDER A 940 23W 38° BLACK | ON/OFF

Article number: N004-K0002-RF940-H5-G38-ZE52_600-S1-###



LED	COB	Spotlig
Light colour	4000 [K]	Track m
CRI	90	possible on enqu power is
Led chip flux	2899 [lm]	
Luminous flux	2609 [lm]	
System power	23 [W]	
Luminaire Efficiency	113 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024