

SPOTLIGHT LIDER A 930 21W 15° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G15-ZE53_550-S1-###





LED COB

Light colour 3000 [K] HI EFFICIENT

CRI

Luminous flux

3138 [lm]

System power 21 [W]

149 [lm/W]

Beam angle 15°

Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Led chip flux

Luminaire Efficiency

Weight 0.7 [kg]

Protection rating IP , IK , class IP 20, IK 01,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-

60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

lic

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

(€ EM 2K

Generated: 24.09.2024





