

SPOTLIGHT

SPOTLIGHT LIDER A 930 23W 38° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G38-ZE53_600-S1-###



	3 SDCM
MacAdam	ON/OFF
Controller	38°
Beam angle	148 [lm/W]
Luminaire Efficiency	23 [W]
System power	
Luminous flux	3408 [lm]
Led chip flux	3787 [lm]
	90
CRI	EFFICIENT
Light colour	3000 [K] HI
LED	COB

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

