

SPOTLIGHT

SPOTLIGHT LIDER A 930 25W 45° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G45-ZE53_650-S1-###



| MacAdam | 3 SDCM |
|----------------------|-------------|
| Controller | ON/OFF |
| | 45° |
| Beam angle | 147 [lm/W] |
| Luminaire Efficiency | 25 [W] |
| System power | 3675 [lm] |
| Luminous flux | 4084 [lm] |
| Led chip flux | 90 |
| CRI | EFFICIENT |
| Light colour | 3000 [K] HI |
| LED | COB |
| | |

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

| Weight | 0,7 [kg] |
|-----------------------------------|------------------|
| Protection rating IP , IK , class | IP 20, IK 1, |
| Luminaire colour | WHITE |
| Cover | Plastic |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024