

SPOTLIGHT LIDER A 930 27W 45° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G45-ZE53_700-S1-###





LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	4378 [lm]
Luminous flux	3940 [lm]
System power	27 [W]
Luminaire Efficiency	146 [lm/W]
Beam angle	45°
Controller MacAdam	ON/OFF
IVIACAUAITI	3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight 0,7 [kg]
Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 23.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska