

# SPOTLIGHT LIDER A 930 31W 45° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G45-ZE53\_800-S1-###



LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	4956 [lm]
Luminous flux	4460 [lm]
System power	31 [W]
Luminaire Efficiency	144 [lm/W]
Beam angle	45°
Controller	ON/OFF
MacAdam	3 SDCM

### Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

### LUMINAIRE

Weight	0.7 [kg]
Protection rating IP , IK , class	IP 20, IK 01,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%  
System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 23.09.2024



+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska

