

SPOTLIGHT LIDER A 930 19W 60° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB930-H5-G60-ZE53_500-S1-###





LED COB

Light colour 3000 [K] HI EFFICIENT

CRI

Led chip flux

Luminous flux

2865 [lm] System power

19 [W] Luminaire Efficiency

151 [lm/W] Beam angle

60° Controller

ON/OFF

3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

LUMINAIRE

MacAdam

Weight 0.7 [kg]

Protection rating IP , IK , class IP 20, IK 01,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-

60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

liC

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

(€ EM 2K

Generated: 24.09.2024





