

## SPOTLIGHT

# SPOTLIGHT LIDER A 940 19W 15° WHITE HI EFFICIENT ON/OFF

Article number: N004-K0003-BB940-H5-G15-ZE53\_500-S1-###



System power	19 [W]
Luminaire Efficiency	6. d
Ream angle	151 [lm/W]
Beam angle	15°
Controller	15°
	ON/OFF
MacAdam	3 SDCM
	3 SDCM

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 31W.

# LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl  $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

