

SPOTLIGHT LIDER A 957 19W 60° WHITE SPECIAL ON/OFF

Article number: N004-K0003-CC957-H5-G60-ZE53_500-S1-###





COB

5700 [K] SPECIAL Light colour

CRI

Led chip flux 2551 [lm] Luminous flux 2295 [lm] System power 19 [W] Luminaire Efficiency 121 [lm/W] Beam angle 60° Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

0,7 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska